



B-B

Voltage Current Rating: 2 AMP.
 Dielectric Withstanding Voltage: 500V
 Insulation Resistance: 500MΩ Min.
 Temperature Range: -25°C to +85°C

ITEM	DESC.	MATERIAL	REMAKS	PART REMAKS
4	SHELL	SPCC T=0.30mm	PLATED NI	
3	HOUSING	PBT+30% UL 94-V0	COLOR:BLACK	
2	COVER	LCP+15% UL 94-V0	COLOR:BLACK	
1	TERMINAL	COPPER ALLOY	CONTACT AREA: G/F SOLDER AREA: Sn UNDER-PLATING: Ni	

A		B		C		D		E		F	
△											
△											
△	2017/01/12 新版发行		King Zhou	QUALITY SYMBOLS	Tolerance	NAME: VHDCI 68P MALE SOLDER (客户用图)		PART NO.	B06-068311A0-01		
SIDE	DATE	DESCRIPTION	APPROVER	CRITICAL MAJOR	.x ±0.80 .x ±0.50 .xx ±0.25	REV: A	UNIT: mm	DRW BY: DAWN HU	CHK BY: KING ZHOU	APP BY:	DRAWING NO. B06-002
8	7	6	5	ZERO DEFECT S.P.C	⊕	lineconn 东莞市林诚塑胶电子有限公司		http://www.lineconn.com		TEL: 0769-85181660 85181770	