




L TYPE



S TYPE



Dimensions:

No. of contacts:	A	B	C	D
26	37.20	31.20	20.25	24.70
36	43.50	37.60	26.60	31.00
50	52.60	46.50	35.40	40.10
68	64.00	57.90	46.93	51.00

• ELECTRICAL CHARACTERISTICS

- Contact Current Rating: 1 Amp
- Dielectric Withstanding Voltage: 500V AC
- Insulation Resistance: 500MΩ/Min
- Contact Resistance: 35mΩ/Max
- Operation Temperature: -25°C ~ +85°C

PART NO:

B03-0XXF18EN-X X

No. OF CONTACTS:

- 26= 26P
- 36= 36P
- 50= 50P
- 68= 68P

PCB MOUNTING:

- A:1.0mm(For PCB 1.2mm)
- B:1.4mm(For PCB 1.6mm)

BRACKET FINISHES:

- L:LATCH BRACKET
- S:SCREW BRACKET

3	HOUSING	PBT+G.F.30% (UL 94V-0)	COLOR: BLACK
2	SHELL	ZINC ALLOY	PLATING: Ni
1	TERMINAL	PHOSPHOR BRONZE	CONTACT AREA: Au 5u" SOLDER AREA: Sn UNDER-PLATING: Ni
ITEM	DESC.	MATERIAL	REMARKS

△				QUALITY SYMBOLS
△				□: ⊠: CRITICAL MAJOR
△	2013/11/09	新版发行	King Zhou	▽: ▽: ZERO DEFECT S.P.C
SIDE	DATE	DESCRIPTION	APPROVER	

Tolerance		NAME:	SCSI FEMALE夹板式 26, 36, 50, 68P (客户用图)			PART NO.	B03-0XXF18EN-X X		
x.	±0.80	REV:	A	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.
.x	±0.50	SCALE:	N:1	DATE:	2013/11/09	JACK CHEN	DEAN FAN		B03-058
.xx	±0.30				东莞市林诚塑胶电子有限公司			http://www.lineconn.com TEL:0769-85181660 85181770	