



Voltage Current Rating: 1.5 AMP.
Dielectric Withstanding Voltage: 500V AC
Insulation Resistance: 100MΩ Min.
Temperature Range: -25°C to +85°C

| 4 | COVERING | COPPER ALLOY | OVER-PLATING: Ni |
|------|----------|-----------------------|---|
| 3 | HOUSING | PBT+30%G.F.(UL 94V-0) | COLOR: BLACK |
| 2 | SHELL | SPCC | OVER-PLATING: Ni |
| 1 | TERMINAL | C5191 | CONTACT AREA: G/F SOLDER AREA: Sn UNDER-PLATING: Ni |
| ITEM | DESC. | MATERIAL | REMAKS |
| | | | PART REMAKS |

| | | | | | | | | | | | | | |
|------|------------|-------------|----------|-------------------|---------------|--------|-------------------------------------|-------|------------|----------|-----------------|--------|-------------|
| | | | | QUALITY SYMBOLS | Tolerance | NAME: | 1394B 9P MALE SOLDER 四件式 铜护套 (客户用图) | | | PART NO. | B19-009311A0-03 | | |
| | | | | □: ☒: | X: ±0.50 | REV: | A | UNIT: | mm | DRW BY | CHK BY | APP BY | DRAWING NO. |
| | | | | CRITICAL MAJOR | .x ±0.30 | SCALE: | N:1 | DATE: | 2011/05/30 | JINGLI | KING ZHOU | | B19-004 |
| | | | | ▽: ▽: | .xx ±0.25 | | | | | | | | |
| | | | | ZERO DEFECT S.P.C | | | | | | | | | |
| △ | 2011/05/30 | NEW ISSUE | JINGLI | | | | | | | | | | |
| SIDE | DATE | DESCRIPTION | APPROVER | | | | | | | | | | |
| 8 | 7 | 6 | 5 | 4 | 3 | 2 | 1 | | | | | | |

lineconn 东莞市林诚塑胶电子有限公司 <http://www.lineconn.com>
 TEL: 0769-85181660 85181770