



PCB Layout

• ELECTRICAL CHARACTERISTICS

- Contact Current Rating: 1 Amp
- Dielectric Withstanding Voltage: 500V AC
- Insulation Resistance: 500MΩ/Min
- Contact Resistance: 35mΩ/Max
- Operaion Temperature: -25°C ~ +85°C

3	HOUSING	PBT+G.F.30% (UL 94V-0)	COLOR: BLACK	
2	SHELL	SPCC	PLATING: Ni	
1	TERMINAL	PHOSPHOR BRONZE	CONTACT AREA: Au 5u" SOLDER AREA: Sn UNDER-PLATING: Ni	
ITEM	DESC.	MATERIAL	REMAKS	PART REMAKS

△				QUALITY SYMBOLS
△				□:    ☒:
△	2009/06/12新版发行		King Zhou	CRITICAL    MAJOR
SIDE	DATE	DESCRIPTION	APPROVER	▽:    ▽: ZERO DEFECT    S.P.C

Tolerance		NAME: SCS1 40P MALE 180° DIP (客户用图)				PART NO. B03-040711EN-01			
x.	±0.80	REV:	A	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO. B03-064
.x	±0.50	SCALE:	N:1	DATE:	2009/06/12	JACK CHEN	DEAN FAN		
.xx	±0.30	<b>东莞市林诚塑胶电子有限公司</b>				<a href="http://www.lineconn.com">http://www.lineconn.com</a> TEL:0769-85181660 85181770			

8 7 6 5 4 3 2 1

F

F

E

E

D

D

C

C

B

B

A

A

8 7 6 5 4 3 2 1