



PCB Layout

• ELECTRICAL CHARACTERISTICS

- Contact Current Rating: 1 Amp
- Dielectric Withstanding Voltage: 500V AC
- Insulation Resistance: 500MΩ/Min
- Contact Resistance: 35mΩ/Max
- Operation Temperature: -25°C ~ +85°C

3	HOUSING	PBT+G.F.30% (UL 94V-0)	COLOR: BLACK	
2	SHELL	SPCC	PLATING: Ni	
1	TERMINAL	PHOSPHOR BRONZE	CONTACT AREA: Au 5u" SOLDER AREA: Sn UNDER-PLATING: Ni	
ITEM	DESC.	MATERIAL	REMARKS	PART REMARKS

△				QUALITY SYMBOLS
△				□: ☒: x: ±0.80
△	2009/06/12新版发行	King Zhou		CRITICAL MAJOR .x ±0.50
SIDE	DATE	DESCRIPTION	APPROVER	ZERO DEFECT S.P.C ∇: ∇: .xx ±0.30

Tolerance		NAME: SCSI 68P MALE 180° DIP		(客户用图)		PART NO.	B03-068711EN-01	
x.	±0.80	REV:	A	UNIT:	mm	DRW BY	CHK BY	APP BY
.x	±0.50	SCALE:	N:1	DATE:	2009/06/12	JACK CHEN	DEAN FAN	DRAWING NO.
.xx	±0.30							B03-066
		lineconn 东莞市林诚塑胶电子有限公司		http://www.lineconn.com		TEL:0769-85181660 85181770		