



PCB LAYOUT

High Power Contact Current Rating:
10,20 or 40AMPS
High Power Contact Resistance:
2.7 Milliohms Max.
Dielectric Withstanding Voltage:
1000V AC For 1 Minute
Insulation Resistance:5000MΩ Min.
Temperature Range:-25°C to +85°C

PART NO:
B08-AW36X14D-X1

HOUSING COLOR:
1:BLACK
3:GREEN
5:WHITE

CURRENT RATING:
A = 10 AMPS Dim.A $\phi 1.7$ Dim.B $\phi 2.2$
B = 20 AMPS Dim.A $\phi 2.8$ Dim.B $\phi 3.3$
C = 30 AMPS Dim.A $\phi 3.2$ Dim.B $\phi 3.7$
D = 40 AMPS Dim.A $\phi 3.7$ Dim.B $\phi 4.2$

6	JACKSCREWS	BRASS	PLATING: Ni	
5	HOUSING	PBT+30%GF	COLOR: WHITE	
4	RIVETED INSERT	BRASS	PLATING: Ni	
3	REAR SHELL	SPCC	PLATING: Sn	
2	FRONT SHELL	SPCC	PLATING: Ni	
1	TERMINAL	BRASS	TERMINAL FINISH: FULL GOLD FINISHED 2u"	
ITEM	DESC.	MATERIAL	REMAKS	PART REMAKS

QUALITY SYMBOLS		Tolerance		NAME: 13W3 90度母头铆支架鱼叉锁螺丝 POWER D-SUB (客户用图)		PART NO. B08-AW36114D-X1	
□:	☒:	x.	±0.50	REV: A	UNIT: mm	CHK BY	APP BY
CRITICAL	MAJOR	.x	±0.30	SCALE: N:1	DATE: 2017/05/13	JINGLI	KING ZHOU
∇:	∇:	.xx	±0.25	http://www.lineconn.com		DRAWING NO. B08-046	
ZERO DEFECTS.P.C				东莞市林诚塑胶电子有限公司		TEL: 0769-85181660 85181770	

△	2017/05/13	NEW ISSUE	JINGLI		
SIDE	DATE	DESCRIPTION	APPROVER		