



PCB LAYOUT

High Power Contact Current Rating:
10,20 or 40AMPS
High Power Contact Resistance:
2.7 Milliohms Max.
Dielectric Withstanding Voltage:
1000V AC For 1 Minute
Insulation Resistance:5000MΩ Min.
Temperature Range:-25°C to +85°C

PART NO:
B08-9W45X14D-X1

HOUSING COLOR:
1:BLACK
3:GREEN
5:WHITE

CURRENT RATING:
A = 10 AMPS Dim.A $\phi 1.7$ Dim.B $\phi 2.2$
B = 20 AMPS Dim.A $\phi 2.8$ Dim.B $\phi 3.3$
C = 30 AMPS Dim.A $\phi 3.2$ Dim.B $\phi 3.7$
D = 40 AMPS Dim.A $\phi 3.7$ Dim.B $\phi 4.2$

6	JACKSCREWS	BRASS	PLATING: Ni	
5	HOUSING	PBT+30%GF	COLOR: WHITE	
4	RIVETED INSERT	BRASS	PLATING: Ni	
3	REAR SHELL	SPCC	PLATING: Sn	
2	FRONT SHELL	SPCC	PLATING: Ni	
1	TERMINAL	BRASS	TERMINAL FINISH: FULL GOLD FINISHED 2u"	
ITEM	DESC.	MATERIAL	REMAKS	PART REMAKS

				QUALITY SYMBOLS	Tolerance	NAME: 9W4 90度公头铆支架鱼叉锁螺丝 POWER D-SUB (客户用图)				PART NO.	B08-9W45114D-X1				
				□: CRITICAL	☒: MAJOR	.x: ±0.50	REV: A				UNIT: mm	DRW BY: JINGLI	CHK BY: KING ZHOU	APP BY:	DRAWING NO. B08-041
				▽: ZERO DEFECTS.P.C	▽: P.C	.x: ±0.30	SCALE: N:1				DATE: 2017/05/08				
						.xx: ±0.25									
SIDE	DATE	DESCRIPTION	APPROVER												
8	7	6	5												

Lineconn 东莞市林诚塑胶电子有限公司 <http://www.lineconn.com>
TEL: 0769-85181660 85181770