



PCB LAYOUT

High Power Contact Current Rating:  
10,20 or 40AMPS  
High Power Contact Resistance:  
2.7 Milliohms Max.  
Dielectric Withstanding Voltage:  
1000V AC For 1 Minute  
Insulation Resistance:5000MΩ Min.  
Temperature Range:-25°C to +85°C

PART NO:  
B08-9W46X14D-X1

HOUSING COLOR:  
1:BLACK  
3:GREEN  
5:WHITE

CURRENT RATING:  
A = 10 AMPS Dim.A ø1.7 Dim.B ø2.2  
B = 20 AMPS Dim.A ø2.8 Dim.B ø3.3  
C = 30 AMPS Dim.A ø3.2 Dim.B ø3.7  
D = 40 AMPS Dim.A ø3.7 Dim.B ø4.2

6	JACKSCREWS	BRASS	PLATING:Ni	
5	HOUSING	PBT+30%GF	COLOR: WHITE	
4	RIVETED INSERT	BRASS	PLATING:Ni	
3	REAR SHELL	SPCC	PLATING:Sn	
2	FRONT SHELL	SPCC	PLATING:Ni	
1	TERMINAL	BRASS	TERMINAL FINISH: FULL GOLD FINISHED 2u"	
ITEM	DESC.	MATERIAL	REMAKS	PART REMAKS

△	2017/05/08	NEW ISSUE	JINGLI
SIDE	DATE	DESCRIPTION	APPROVER
8	7	6	5

QUALITY SYMBOLS	Tolerance
□:    ☒:	x.    ±0.50
CRITICAL MAJOR	.x    ±0.30
▽:    ▽:	.xx   ±0.25
ZERO DEFECTS.P.C	

NAME:	9W4 90度母头铆支架鱼叉锁螺丝 POWER D-SUB (客户用图)				PART NO.	B08-9W46114D-X1		
REV:	A	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.	
SCALE:	N:1	DATE:	2017/05/08	JINGLI	KING ZHOU		B08-041	
Lineconn 东莞市林诚塑胶电子有限公司				http://www.lineconn.com		TEL: 0769-85181660 85181770		
8	7	6	5	4	3	2	1	