






Termination Cover  
(1 Places)



Wire Holder  
(2 Places)



- Current Rating: 1 Amp
- Insulation Resistance: 500MΩ/Min
- Withstanding Voltage: 500V AC/Min
- Contact Resistance: 35mΩ Max
- Operation Temperature: -25°C ~ +85°C

PART NO: B02-026111E0-X0

WIRE HOLDER: \_\_\_\_\_  
 28AWG or 30AWG WIRE  
 6= 0.62mm  
 7= 0.75mm  
 9= 0.90mm

4	COVER	PBT+G.F.30% (UL 94V-0)	COLOR: BLACK
3	HOUSING	PBT+G.F.30% (UL 94V-0)	COLOR: BLACK
2	SHELL	SPCC	PLATING: Ni
1	TERMINAL	PHOSPHOR BRONZE	CONTACT AREA: Au 5u" SOLDER AREA: Sn UNDER-PLATING: Ni
ITEM	DESC.	MATERIAL	REMAKS
			PART REMAKS

△			QUALITY SYMBOLS
△			□:    ☒:
△	2008/08/12 新版发行	King Zhou	CRITICAL MAJOR
SIDE	DATE	DESCRIPTION	APPROVER
8	7	6	5

Tolerance		NAME:	SCSI PIN TYPE 26P MALE IDC刺破式 ASSEMBLY CONN. (客户用图)				PART NO.	B02-026111E0-X0	
x.	±0.80	REV:	A	UNIT:	mm	DRW BY	CHK BY	APP BY	
.x	±0.50	SCALE:	N:1	DATE:	2008/08/12	JACK CHEN	DEAN FAN	DRAWING NO.	
.xx	±0.30							B02-028	
		东莞市林诚塑胶电子有限公司				<a href="http://www.lineconn.com">http://www.lineconn.com</a> TEL:0769-85181660 85181770			
4	3	2	1						