


Termination Cover
(1 Places)



Wire Holder
(2 Places)

- Current Rating: 1 Amp
- Insulation Resistance: 500MΩ/Min
- Withstanding Voltage: 500V AC/Min
- Contact Resistance: 35mΩ Max
- Operation Temperature: -25°C ~ +85°C

PART NO: B02-020111E0-X0

WIRE HOLDER: _____
 28AWG or 30AWG WIRE
 6= 0.62mm
 7= 0.75mm
 9= 0.90mm

4	COVER	PBT+G.F.30% (UL 94V-0)	COLOR: BLACK	
3	HOUSING	PBT+G.F.30% (UL 94V-0)	COLOR: BLACK	
2	SHELL	SPCC	PLATING: Ni	
1	TERMINAL	PHOSPHOR BRONZE	CONTACT AREA: Au 5u" SOLDER AREA: Sn UNDER-PLATING: Ni	
ITEM	DESC.	MATERIAL	REMAKS	PART REMAKS

A	△			QUALITY SYMBOLS
	△			□: ☒:
	△	2008/08/12 新版发行	King Zhou	CRITICAL MAJOR
	SIDE	DATE	DESCRIPTION	APPROVER
	8	7	6	5

Tolerance		NAME: SCSI PIN TYPE 20P MALE IDC刺破式 ASSEMBLY CONN. (客户用图)		PART NO.	B02-020111E0-X0	
x.	±0.80	REV:	A	UNIT:	mm	DRW BY
.x	±0.50	SCALE:	N:1	DATE:	2008/08/12	JACK CHEN
.xx	±0.30					DEAN FAN
				Lineconn 东莞市林诚塑胶电子有限公司		http://www.lineconn.com TEL:0769-85181660 85181770
	4		3		2	1