



Voltage Current Rating:0.5AMP
 Dielectric Withstanding Voltage:150V AC
 Contact Resistance:40 mΩ Max.
 Insulation Resistance:500MΩ Min.
 Temperature Range:-20℃ to +85℃

5	BRACKET	ZINC	PLATING:Ni	
4	COVER	PA-9T	COLOR:BLACK	
3	HOUSING	PA-9T	COLOR:BLACK	
2	SHELL	SPCC	PLATING:Ni	
1	TERMINAL	PHOSPHOR BRONZE	CONTACT AREA: Au 5u" SOLDER AREA: Sn UNDER-PLATING: Ni	
ITEM	DESC.	MATERIAL	REMARKS	PART REMARKS

△			
△			
△	2015/04/09新版发行	King Zhou	
SIDE	DATE	DESCRIPTION	APPROVER
8	7	6	5

QUALITY SYMBOLS		Tolerance	
□:	☒:	x.	±0.80
CRITICAL	MAJOR	.x	±0.50
▽:	▽:	.xx	±0.25
ZERO DEFECT	S.P.C		

NAME: SCS1 26P FEMALE SMT (客户用图)				PART NO.	B03-026011EB-01	
REV:	A	UNIT:	mm	DRW BY	CHK BY	APP BY
SCALE:	N:1	DATE:	2015/04/09	DAWN HU	KING ZHOU	
东莞市林诚塑胶电子有限公司				http://www.lineconn.com TEL:0769-85181660 85181770		
3	2	1				