



No. of Contact	A ±0.25	B ±0.13	C ±0.38	D ±0.13	E ±0.25
15	16.33	24.99	33.98	39.58	33.98
26	24.66	33.32	42.30	47.90	42.30
44	38.38	47.04	56.02	61.62	55.92

Voltage Current Rating:5 AMP.
 Contact Resistance: 15mΩ MAX
 Dielectric Withstanding Voltage:1000V AC
 Insulation Resistance:5GΩ Min.
 Temperature Range:-25℃ to +85℃
 Degree Of Protection:IP68 Accord

PART NO: BA4-0XX411AN-01

NO.OF CONTACT:
 15 = 15 PIN
 26 = 26 PIN
 44 = 44 PIN

6	EPOXY SEALANT	EPOXY		
5	O-RING	SILICONE		
4	REAR SHELL	SPCC	PALTING: Sn	
3	FRONT SHELL	SPCC	PALTING: Ni	
2	HOUSING	PBT+30%GF	COLOR: BLACK	
1	TERMINAL	COPPER ALLOY	CONTACT AREA: G/F SOLDER AREA: Sn	
ITEM	DESC.	MATERIAL	REMARKS	PART REMARKS

QUALITY SYMBOLS		Tolerance		NAME: 防水HD. D-SUB母头焊线式 (客户用图)				PART NO.	BA4-0XX411AN-01		
□ :	☒ :	x.	±0.50	REV:	A	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.
CRITICAL	MAJOR	.x	±0.30	SCALE:	N:1	DATE:	2015/07/16	JINGLI	KING ZHOU		BA4-002
▽ :	▽ :	.xx	±0.25	东莞市林诚塑胶电子有限公司				http://www.lineconn.com TEL:0769-85181660 85181770			
ZERO DEFECT	S.P.C										

SIDE	DATE	DESCRIPTION	APPROVER
△	2015/07/16	NEW ISSUE	JINGLI