



**Voltage Current Rating: 5 AMP.**  
**Dielectric Withstanding Voltage: 500V AC**  
 Insulation Resistance: 1000MΩ Min.  
 Temperature Range: -25°C to +85°C  
 PART NO: B17-0XX3X1AF-01  
 CONTACT NO.:  
 14: 14PIN  
 24: 24PIN  
 36: 36PIN  
 50: 50PIN  
 HOUSING COLOR:  
 1:BLACK  
 6:BLUE

Positions	A±0.3	B±0.35	C±0.35	D±0.25	E±0.25	F±0.4
14	25.3	37.9	15.8	7.0	17.45	25.44
24	36.0	49.0	15.8	9.0	28.35	36.24
36	49.3	61.6	15.8	11.5	41.35	49.2
50	64.2	77.1	16	12.5	56.35	64.32

ITEM	DESC.	MATERIAL	REMARKS	PART REMARKS
3	HOUSING	PBT+30%G.F.(UL 94V-0)	COLOR: SEE PART NO.	
2	SHELL	SPCC	OVER-PLATING: Ni	
1	TERMINAL	COPPER ALLOY	CONTACT AREA: G/F SOLDER AREA: Sn UNDER-PLATING: Ni	

△	2012/07/12	NEW ISSUE	JINGLI
SIDE	DATE	DESCRIPTION	APPROVER
8	7	6	5

QUALITY SYMBOLS		Tolerance	
□:	☒:	x.	±0.50
CRITICAL	MAJOR	.x	±0.30
▽:	▽:	.xx	±0.25
ZERO DEFECT	S.P.C		

NAME:		57-传统公焊线式+30大铁壳 (客户用图)				PART NO.	B17-0XX3X1AF-01	
REV:	A	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.	
SCALE:	N:1	DATE:	2012/07/12	JINGLI	KING ZHOU		B17-002	
东莞市林诚塑胶电子有限公司				<a href="http://www.lineconn.com">http://www.lineconn.com</a> TEL:0769-85181660 85181770				
3	2	1	8	7	6	5	4	3