



• ELECTRICAL CHARACTERISTICS

Contact Current Rating: 1 Amp
 Dielectric Withstanding Voltage: 500V AC
 Insulation Resistance: 500MΩ/Min
 Contact Resistance: 35mΩ/Max
 Operation Temperature: -25°C ~ +85°C

4	COVER	PBT+G.F.30% (UL 94V-0)	COLOR:BLACK	
3	HOUSING	PBT+G.F.30% (UL 94V-0)	COLOR:BLACK	
2	SHELL	SPCC	PLATING:Ni	
1	TERMINAL	PHOSPHOR BRONZE	CONTACT AREA: Au 5u" SOLDER AREA: Sn UNDER-PLATING: Ni	
ITEM	DESC.	MATERIAL	REMAKS	PART REMAKS

△				QUALITY SYMBOLS
△				□: ☒:
△	2010/12/11	新版发行	King Zhou	CRITICAL MAJOR
SIDE	DATE	DESCRIPTION	APPROVER	ZERO DEFECT S.P.C

Tolerance		NAME:	SCSI 50P MALE SOLDER ASSEMBLY CONN. (客户用图)			PART NO.	B03-050311E0-01	
x.	±0.80	REV:	A	UNIT:	mm	DRW BY	CHK BY	APP BY
.x	±0.50	SCALE:	N:1	DATE:	2010/12/11	JACK CHEN	DEAN FAN	DRAWING NO.
.xx	±0.30	东莞市林诚塑胶电子有限公司						B03-072
						http://www.lineconn.com TEL:0769-85181660 85181770		

