



Termination Cover  
(1 Places)



Wire Holder  
(2 Places)

- Current Rating: 1 Amp
- Insulation Resistance: 500MΩ/Min
- Withstanding Voltage: 500V AC/Min
- Contact Resistance: 35mΩ Max
- Operation Temperature: -25°C ~ +85°C

PART NO: B03-040111E0-X0

WIRE HOLDER: \_\_\_\_\_  
 28AWG or 30AWG WIRE  
 6= 0.62mm  
 7= 0.75mm  
 9= 0.90mm

ITEM	DESC.	MATERIAL	REMARKS	PART REMARKS
4	COVER	PBT+G.F.30% (UL 94V-0)	COLOR: BLACK	
3	HOUSING	PBT+G.F.30% (UL 94V-0)	COLOR: BLACK	
2	SHELL	SPCC	PLATING: Ni	
1	TERMINAL	PHOSPHOR BRONZE	CONTACT AREA: Au 5u" SOLDER AREA: Sn UNDER-PLATING: Ni	

△				QUALITY SYMBOLS	Tolerance	NAME:	SCSI 40P MALE IDC刺破式 ASSEMBLY CONN. (客户用图)				PART NO.	B03-040111E0-X0	
△				□:    ⊠:	x.    ±0.80	REV:	A	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.
△	2010/01/09	新版发行	King Zhou	CRITICAL    MAJOR	.x    ±0.50	SCALE:	N:1	DATE:	2010/01/09	JACK CHEN	DEAN FAN		B03-069
SIDE	DATE	DESCRIPTION	APPROVER	▽:    ▽:	.xx    ±0.30	lineconn 东莞市林诚塑胶电子有限公司				http://www.lineconn.com TEL:0769-85181660 85181770			
8	7	6	5	ZERO DEFECT    S.P.C		4	3	2	1				