



• ELECTRICAL CHARACTERISTICS

Contact Current Rating: 1 Amp
 Dielectric Withstanding Voltage: 500V AC
 Insulation Resistance: 500MΩ/Min
 Contact Resistance: 35mΩ/Max
 Operation Temperature: -25°C ~ +85°C

4	COVER	PBT+G.F.30% (UL 94V-0)	COLOR: BLACK	
3	HOUSING	PBT+G.F.30% (UL 94V-0)	COLOR: BLACK	
2	SHELL	SPCC	PLATING: Ni	
1	TERMINAL	PHOSPHOR BRONZE	CONTACT AREA: Au 5u" SOLDER AREA: Sn UNDER-PLATING: Ni	
ITEM	DESC.	MATERIAL	REMARKS	PART REMARKS

△				
△				
△	2010/01/09	新版发行	King Zhou	
SIDE	DATE	DESCRIPTION	APPROVER	
8	7	6	5	4

QUALITY SYMBOLS		Tolerance		NAME:		SCSI 40P MALE SOLDER ASSEMBLY CONN. (客户用图)		PART NO.		B03-040311E0-01	
□:	⊗:	x.	±0.80	REV:	A	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.
CRITICAL	MAJOR	.x	±0.50	SCALE:	N:1	DATE:	2010/01/09	JACK CHEN	DEAN FAN		B03-070
▽:	▽:	.xx	±0.30			东莞市林诚塑胶电子有限公司		http://www.lineconn.com		TEL:0769-85181660 85181770	
ZERO DEFECT	S.P.C										
8	7	6	5	4	3	2	1				