



• ELECTRICAL CHARACTERISTICS

- Contact Current Rating: 1 Amp
- Dielectric Withstanding Voltage: 500V AC
- Insulation Resistance: 500MΩ/Min
- Contact Resistance: 35mΩ/Max
- Operaion Temperature: -25°C ~ +85°C

4	COVER	PBT+G.F.30% (UL 94V-0)	COLOR:BLACK	
3	HOUSING	PBT+G.F.30% (UL 94V-0)	COLOR:BLACK	
2	SHELL	SPCC	PLATING:Ni	
1	TERMINAL	PHOSPHOR BRONZE	CONTACT AREA:Au 5u" SOLDER AREA:Sn UNDER-PLATING:Ni	
ITEM	DESC.	MATERIAL	REMAKS	PART REMAKS

△				QUALITY SYMBOLS
△				□:    ☒:
△	2008/08/12新版发行		King Zhou	CRITICAL    MAJOR
SIDE	DATE	DESCRIPTION	APPROVER	▽:    ▽: ZERO DEFECT    S.P.C
8	7	6	5	

Tolerance		NAME: SCS1 36P MALE SOLDER ASSEMBLY CONN. (客户用图)		PART NO.	B03-036311E0-01				
x.	±0.80	REV:	A	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.
.x	±0.50	SCALE:	N:1	DATE:	2008/08/12	JACK CHEN	DEAN FAN		B03-060
.xx	±0.30	东莞市林诚塑胶电子有限公司		<a href="http://www.lineconn.com">http://www.lineconn.com</a>		TEL:0769-85181660 85181770			
4	3	2	1						