

F









E

D



C

B

A



Termination Cover
(1 Places)



Wire Holder
(2 Places)

- Current Rating: 1 Amp
- Insulation Resistance: 500MΩ/Min
- Withstanding Voltage: 500V AC/Min
- Contact Resistance: 35mΩ Max
- Operation Temperature: -25°C ~ +85°C

PART NO: B03-026111E0-X0

WIRE HOLDER: _____
 28AWG or 30AWG WIRE
 6= 0.62mm
 7= 0.75mm
 9= 0.90mm

4	COVER	PBT+G.F.30% (UL 94V-0)	COLOR:BLACK	
3	HOUSING	PBT+G.F.30% (UL 94V-0)	COLOR:BLACK	
2	SHELL	SPCC	PLATING:Ni	
1	TERMINAL	PHOSPHOR BRONZE	CONTACT AREA:Au 5u” SOLDER AREA:Sn UNDER-PLATING:Ni	
ITEM	DESC.	MATERIAL	REMAKS	PART REMAKS

△				QUALITY SYMBOLS
△				□: ☒: x. ±0.80
△	2008/08/12	新版发行	King Zhou	CRITICAL MAJOR .x ±0.50
SIDE	DATE	DESCRIPTION	APPROVER	ZERO DEFECT S.P.C ∇: ∇: .xx ±0.30

Tolerance		NAME: SCSII 26P MALE IDC刺破式 ASSEMBLY CONN. (客户用图)		PART NO.	B03-026111E0-X0	
REV:	A	UNIT:	mm	DRW BY	CHK BY	APP BY
SCALE:	N:1	DATE:	2008/08/12	JACK CHEN	DEAN FAN	DRAWING NO. B03-055
东莞市林诚塑胶电子有限公司				http://www.lineconn.com TEL:0769-85181660 85181770		