



**Termination Cover
(1 Places)**



**Wire Holder
(2 Places)**

- Current Rating: 1 Amp
- Insulation Resistance: 500MΩ/Min
- Withstanding Voltage: 500V AC/Min
- Contact Resistance: 35mΩ Max
- Operation Temperature: -25°C ~ +85°C

PART NO: B03-020111E0-X0

WIRE HOLDER:
28AWG or 30AWG WIRE
6= 0.62mm
7= 0.75mm
9= 0.90mm

4	COVER	PBT+G.F.30% (UL 94V-0)	COLOR: BLACK	
3	HOUSING	PBT+G.F.30% (UL 94V-0)	COLOR: BLACK	
2	SHELL	SPCC	PLATING: Ni	
1	TERMINAL	PHOSPHOR BRONZE	CONTACT AREA: Au 5u" SOLDER AREA: Sn UNDER-PLATING: Ni	
ITEM	DESC.	MATERIAL	REMARKS	PART REMARKS

△				QUALITY SYMBOLS
△				□: ☒:
△	2008/08/12新版发行		King Zhou	CRITICAL MAJOR
SIDE	DATE	DESCRIPTION	APPROVER	▽: ▽:
8	7	6	5	ZERO DEFECT S.P.C

Tolerance		NAME:		SCSI 20P MALE IDC刺破式 ASSEMBLY CONN. (客户用图)		PART NO.		B03-020111E0-X0	
x.	±0.80	REV:	A	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.
.x	±0.50	SCALE:	N:1	DATE:	2008/08/12	JACK CHEN	DEAN FAN		B03-047
.xx	±0.30	lineconn 东莞市林诚塑胶电子有限公司		http://www.lineconn.com		TEL:0769-85181660 85181770			
4		3		2		1			