



- Current Rating: 1 Amp
- Insulation Resistance: 500MΩ/Min
- Withstanding Voltage: 500V AC/Min
- Contact Resistance: 35mΩ Max
- Temperature Range: -25°C ~ +85°C

PART NO:

BXX-068NN8N3-XX

SPECIFICATION:

02:HPDB

03:HPCN

ENTRY HOLE SIZES:

1A:φ10.0

1D:φ14.0

2D:24mm方型孔 2*4

ITEM	DESC.	MATERIAL	REMARKS	PART REMARKS
4	SPRING LATCH	STAINLESS STEEL		
3	CABLE CLIPPER	STEEL	PLATING:NI	
2	FLAT SCREWS	STEEL	PLATING:NI	
1	BACK SHELL	ZINC ALLOY	PLATING:NI	

QUALITY SYMBOLS

□: ☒: CRITICAL MAJOR
 ZERO DEFECT S.P.C

Tolerance

x: ±0.50
 .x ±0.30
 .xx ±0.25

NAME:

SCSI 68P MALE 锌合金组装外壳弹片式
 (客户用图)

PART NO.

BXX-068NN8N3-XX

REV:

A

UNIT:

mm

DRW BY

CHK BY

APP BY

DRAWING NO.

SCALE:

N:1

DATE:

2012/07/22

JINGLI

KING ZHOU

BXX-A09

lineconn

东莞市林诚塑胶电子有限公司

<http://www.lineconn.com>

TEL:0769-85181660 85181770

△ 2012/07/22

NEW ISSUE

JINGLI

SIDE DATE

DESCRIPTION

APPROVER

8

7

6

5

4

3

2

1