

No.of Contact	A	B	C	D	E	F
15	16.3	25.0	30.8	2.29	0.25	0.89
26	24.7	33.3	39.1	2.29	0.51	0.64
44	38.4	47.0	53.0	2.29	0.51	0.64
62	54.8	63.5	69.3	2.41	0.58	0.62

Voltage Current Rating:5 AMP.  
 Dielectric Withstanding Voltage:1000V AC  
 Insulation Resistance:1000MΩ Min.  
 Temperature Range:-25℃ to +85℃

PART NO:  
 B04-0XX611AD-F4

NO.OF CONTACT:  
 15 = 15 pos  
 26 = 26 pos  
 37 = 37 pos  
 62 = 62 pos

ITEM	DESC.	MATERIAL	REMARKS	PART REMARKS
6	RIVET	COPPER ALLOY	PALTING: Ni	
5	SCREW	STEEL	PALTING: Ni	
4	BOARDLOCK	COPPER ALLOY	PALTING: Ni	
3	HOUSING	PBT+30%GF	COLOR: BLACK	
2	SHELL	SPCC	PALTING: Ni	
1	TERMINAL	COPPER ALLOY	CONTACT AREA: G/F SOLDER AREA: Sn UNDER-PLATING: Ni	

QUALITY SYMBOLS

Tolerance

NAME:

HD. D-SUB FEMALE 90度DIP 8.89mm  
前锁4.8mm螺母 (客户用图)

PART NO.

B04-0XX611AD-F4

REV:

A

UNIT:

mm

DRW BY

CHK BY

APP BY

DRAWING NO.

SCALE:

N:1

DATE:

2011/03/07


JINGLI

KING ZHOU

B04-016

CRITICAL MAJOR

ZERO DEFECTS.P.C



东莞市林诚塑胶电子有限公司

http://www.lineconn.com

TEL: 0769-85181660 85181770

NEW ISSUE

2011/03/07

DESCRIPTION

JINGLI

APPROVER

SIDE

8

7

6

5

4

3

2

1