



ELECTRICAL CHARACTERISTICS

- Contact Current Rating: 1 Amp
- Dielectric Withstanding Voltage: 500V AC
- Insulation Resistance: 500MΩ/Min
- Contact Resistance: 35mΩ/Max
- Operation Temperature: -25°C ~ +85°C

PART NO.:

B03-02031X X0-M1

SHELL PLATED:

- 1:Ni
- 2:G/F

CONTACT AREA:

- A:G/F
- E:Au 5u"

4	COVER	PBT+G.F.30% (UL 94V-0)	COLOR: BLACK	
3	HOUSING	PBT+G.F.30% (UL 94V-0)	COLOR: BLACK	
2	SHELL	SPCC (t=0.50mm)	PLATING: SEE P/N:	
1	TERMINAL	COPPER ALLOY (t=0.25mm)	CONTACT AREA: P/N SOLDER AREA: Sn UNDER-PLATING: Ni	
ITEM	DESC.	MATERIAL	REMARKS	PART REMARKS

△			
△			
△	2017/10/09 新版发行	KING ZHOU	
SIDE	DATE	DESCRIPTION	APPROVER
8	7	6	5

QUALITY SYMBOLS	
□:	☒:
CRITICAL	MAJOR
▽:	▽:
ZERO DEFECT	S.P.C

Tolerance	
x.	±0.80
.x	±0.50
.xx	±0.30

NAME:		SCSI 20P MALE SOLDER MOLDED TYPE (客户用图)				PART NO.	B03-02031XX0-M1		
REV:	A	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.		
SCALE:	N:1	DATE:	2017/10/09	JACK CHEN	KING ZHOU		B03-082		
东莞市林诚塑胶电子有限公司				http://www.lineconn.com TEL:0769-85181660 85181770					
4	3	2	1						