



ELECTRICAL CHARACTERISTICS

- Contact Current Rating: 1 Amp
- Dielectric Withstanding Voltage: 500V AC
- Insulation Resistance: 500MΩ/Min
- Contact Resistance: 35mΩ/Max
- Operation Temperature: -25°C ~ +85°C

PART NO.:

B03-02631X X0-M1

SHELL PLATED:

- 1:Ni
 - 2:G/F
- CONTACT AREA:**
- A:G/F
 - E:Au 5u"

4	COVER	PBT+G.F.30% (UL 94V-0)	COLOR: BLACK
3	HOUSING	PBT+G.F.30% (UL 94V-0)	COLOR: BLACK
2	SHELL	SPCC (t=0.50mm)	PLATING: SEE P/N:
1	TERMINAL	COPPER ALLOY (t=0.25mm)	CONTACT AREA: P/N SOLDER AREA: Sn UNDER-PLATING: Ni
ITEM	DESC.	MATERIAL	REMARKS

△			
△			
△	2008/07/08 新版发行		King Zhou
SIDE	DATE	DESCRIPTION	APPROVER
8	7	6	5

QUALITY SYMBOLS		Tolerance		NAME: SCSI 26P MALE SOLDER MOLDED TYPE (客户用图)		PART NO. B03-02631XX0-M1	
□: CRITICAL	☒: MAJOR	x. ±0.80	REV: A	UNIT: mm	DRW BY	CHK BY	APP BY
▽: ZERO DEFECT	▽: S.P.C	.x ±0.50	SCALE: N:1	DATE: 2008/07/08	DAW NHU	KING ZHOU	DRAWING NO. B03-036
		.xx ±0.30	东莞市林诚塑胶电子有限公司		http://www.lineconn.com TEL:0769-85181660 85181770		
			4	3	2	1	