



- ELECTRICAL CHARACTERISTICS**
 - Contact Current Rating: 1 Amp
 - Dielectric Withstanding Voltage: 500V AC
 - Insulation Resistance: 500MΩ/Min
 - Contact Resistance: 35mΩ/Max
 - Operation Temperature: -25°C ~ +85°C

PART NO.:
 B03-01431X X0-M1
 SHELL PLATED: _____
 1:Ni
 2:G/F
 CONTACT AREA: _____
 A:G/F
 E:Au 5u"

4	COVER	PBT+G.F.30% (UL 94V-0)	COLOR: BLACK
3	HOUSING	PBT+G.F.30% (UL 94V-0)	COLOR: BLACK
2	SHELL	SPCC (t=0.50mm)	PLATING: SEE P/N:
1	TERMINAL	COPPER ALLOY (t=0.25mm)	CONTACT AREA: P/N SOLDER AREA: Sn UNDER-PLATING: Ni
ITEM	DESC.	MATERIAL	REMARKS

Tolerance x. ±0.80 .x ±0.50 .xx ±0.30		NAME: SCS1 14P MALE SOLDER MOLDED TYPE (客户用图)		PART NO. B03-01431XX0-M1	
CRITICAL MAJOR ZERO DEFECT S.P.C		REV: A SCALE: N:1	UNIT: mm DATE: 2008/07/05	DRW BY: DAW NHU KING ZHOU	APP BY: _____ DRAWING NO. B03-022
		东莞市林诚塑胶电子有限公司		http://www.lineconn.com TEL: 0769-85181660 85181770	

△				QUALITY SYMBOLS □: ☒: CRITICAL MAJOR ZERO DEFECT S.P.C
△	2008/07/05	新版发行	King Zhou	
SIDE	DATE	DESCRIPTION	APPROVER	