



No.of Contact	A	B	C	D
09	16.2	25.0	30.8	19.0
15	24.8	33.3	39.2	27.7
25	38.3	47.0	53.0	41.0
37	54.8	63.5	69.4	57.3

Voltage Current Rating:5 AMP.
 Dielectric Withstanding Voltage:1000V AC
 Insulation Resistance:1000MΩ Min.
 Temperature Range:-25℃ to +85℃

PART NO: B05-0XX8X1AD-E5

NO.OF CONTACT:
 09 = 9 pos
 15 = 15 pos
 25 = 25 pos
 37 = 37 pos

HOUSING COLOR:
 1 = BLACK
 5 = WHITE
 6 = BLUE

ITEM	DESC.	MATERIAL	REMARKS	PART REMARKS
6	SCREW	STEEL	PALTING: Ni	
5	BOARDLOCK	COPPER ALLOY	PALTING: Ni	
4	HOUSING	PBT+30%GF	COLOR: SEE PART NO.	
3	REAR SHELL	SPCC	PALTING: Sn	
2	FRONT SHELL	SPCC	PALTING: Ni	
1	TERMINAL	COPPER ALLOY	CONTACT AREA: G/F SOLDER AREA: Sn UNDER-PLATING: Ni	

SIDE	DATE	DESCRIPTION	APPROVER
△	2014/09/02	NEW ISSUE	JINGLI

QUALITY SYMBOLS	Tolerance
□: ☒:	.x ±0.50
CRITICAL MAJOR	.x ±0.30
▽: ▽:	.xx ±0.25
ZERO DEFECTS.P.C	

NAME:	D-SUB FEMALE 180度后铆6.0鱼叉前锁5.0mm螺母 (客户用图)				PART NO.	B05-0XX8X1AD-E5		
REV:	A	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.	
SCALE:	N:1	DATE:	2014/09/02	JINGLI	KING ZHOU		B05-091	
东莞市林诚塑胶电子有限公司				http://www.lineconn.com TEL: 0769-85181660 85181770				