

PCB LAYOUT

No.of Contact	A	B	C	D
09	16.2	25.0	30.8	19.15
15	24.8	33.3	39.2	27.51
25	38.3	47.0	53.0	41.28
37	54.8	63.5	69.4	57.71

Voltage Current Rating:5 AMP.
 Dielectric Withstanding Voltage:1000V AC
 Insulation Resistance:1000MΩ Min.
 Temperature Range:-25°C to +85°C

PART NO:
 B05-0XX8X1AD-G5

NO.OF CONTACT:
 09 = 9 pos
 15 = 15 pos
 25 = 25 pos
 37 = 37 pos


6	SCREW	STEEL	PALTING:Ni	
5	BOARDLOCK	COPPER ALLOY	PALTING:Ni	
4	HOUSING	PBT+30%GF	COLOR:BLACK	
3	REAR SHELL	SPCC	PALTING:Sn	
2	FRONT SHELL	SPCC	PALTING:Ni	
1	TERMINAL	COPPER ALLOY	CONTACT AREA:G/F SOLDER AREA:Sn UNDER-PLATING:Ni	
ITEM	DESC.	MATERIAL	REMARKS	PART REMARKS

QUALITY SYMBOLS

□: ☒:
 CRITICAL MAJOR
 ▼: ▼:
 ZERO DEFECT S.P.C

Tolerance

.x ±0.50
 .x ±0.30
 .xx ±0.25



NAME:	D-SUB FEMALE 180度后铆20.2鱼叉前锁5.0mm螺母 (客户用图)				PART NO.	B05-0XX8X1AD-G5		
REV:	A	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.	
SCALE:	N:1	DATE:	2018/05/30	JINGLI	KING ZHOU		B05-095	

lineconn 东莞市林诚塑胶电子有限公司 <http://www.lineconn.com>
 TEL:0769-85181660 85181770

△	2018/05/30	NEW ISSUE	JINGLI
SIDE	DATE	DESCRIPTION	APPROVER