



High Power Contact Current Rating:
10,20 or 40AMPS
High Power Contact Resistance:
2.7 Milliohms Max.
Dielectric Withstanding Voltage:
1000V AC For 1 Minute
Insulation Resistance:5000MΩ Min.
Temperature Range:-25°C to +85°C

PART NO:
B08-9W431140-X1

Current Rating: _____
A = 10 AMPS Dim.A ϕ 1.70
B = 20 AMPS Dim.A ϕ 2.80
C = 30 AMPS Dim.A ϕ 3.20
D = 40 AMPS Dim.A ϕ 4.60

4	HOUSING	PBT+30%GF	COLOR:BLACK	
3	REAR SHELL	SPCC	PLATING:Sn	
2	FRONT SHELL	SPCC	PLATING:Ni	
1	TERMINAL	BRASS	TERMINAL FINISH:FULL GOLD FINISHED 2u"	
ITEM	DESC.	MATERIAL	REMAKS	PART REMAKS

				QUALITY SYMBOLS	Tolerance	NAME: 9W4公头焊线式光孔 POWER D-SUB (客户用图)				PART NO.	B08-9W431140-X1		
				□: CRITICAL	x. ±0.50	REV: A	UNIT: mm	DRW BY: JINGLI	CHK BY: KING ZHOU	APP BY:	DRAWING NO. B08-015		
				⊠: MAJOR	.x ±0.30	SCALE: N:1	DATE: 2012/11/19						
				▽: ZERO DEFECT	.xx ±0.25	Lineconn 东莞市林诚塑胶电子有限公司						http://www.lineconn.com	
				▽: S.P.C		TEL:0769-85181660 85181770							
SIDE	DATE	DESCRIPTION		APPROVER									
8	2012/11/19	NEW ISSUE		JINGLI									