



PCB LAYOUT

High Power Contact Current Rating:  
10,20 or 40AMPS  
High Power Contact Resistance:  
2.7 Milliohms Max.  
Dielectric Withstanding Voltage:  
1000V AC For 1 Minute  
Insulation Resistance:5000MΩ Min.  
Temperature Range:-25°C to +85°C

PART NO:  
B08-3W36114D-X1

Current Rating: \_\_\_\_\_  
A = 10 AMPS Dim.A  $\phi$ 1.7 Dim.B  $\phi$ 2.2  
B = 20 AMPS Dim.A  $\phi$ 2.8 Dim.B  $\phi$ 3.3  
C = 30 AMPS Dim.A  $\phi$ 3.2 Dim.B  $\phi$ 3.7  
D = 40 AMPS Dim.A  $\phi$ 3.7 Dim.B  $\phi$ 4.2

6	JACKSCREWS	BRASS	PLATING: Ni	
5	HOUSING	PBT+30%GF	COLOR: WHITE	
4	RIVETED INSERT	BRASS	PLATING: Ni	
3	REAR SHELL	SPCC	PLATING: Sn	
2	FRONT SHELL	SPCC	PLATING: Ni	
1	TERMINAL	BRASS	TERMINAL FINISH: FULL GOLD FINISHED 2u"	

QUALITY SYMBOLS

□:  MAJOR

⊠:  CRITICAL

∇:  ZERO DEFECT

S.P.C

Tolerance

X: ±0.50

.X: ±0.30

.XX: ±0.25



A	DATE	2012/11/19	DESCRIPTION	NEW ISSUE	APPROVER	JINGLI
8	SIDE	8	7	6	5	4

NAME: 3W3 90度母头铆架黑铜叉锁螺丝 (客户用图) POWER D-SUB

REV: A UNIT: mm DRW BY: JINGLI CHK BY: KING ZHOU APP BY: B08-026

SCALE: N:1 DATE: 2012/11/19

http://www.lineconn.com

lineconn 东莞市林城塑胶电子有限公司 TEL:0769-85181660 85181770