



No. of Contact	A	B	C	D
09	16.9	25.0	30.8	19.0
15	25.3	33.3	39.2	27.7
25	39.0	47.0	53.0	41.0
37	55.4	63.5	69.4	57.3

Voltage Current Rating: 5 AMP.
Dielectric Withstanding Voltage: 1000V AC
 Insulation Resistance: 1000MΩ Min.
 Temperature Range: -25°C to +85°C

PART NO: B05-0XX3X1A0-F5

NO.OF CONTACT:
 09 = 9 pos
 15 = 15 pos
 25 = 25 pos
 37 = 37 pos

HOUSING COLOR:
 1 = BLACK
 5 = WHITE
 6 = BLUE

ITEM	DESC.	MATERIAL	REMARKS	PART REMARKS
5	SCREW	STEEL	PALTING: Ni	
4	REAR SHEEL	SPCC	PALTING: Sn	
3	FRONT SHEEL	SPCC	PALTING: Ni	
2	HOUSING	PBT+30%GF	COLOR: SEE PART NO.	
1	TERMINAL	COPPER ALLOY	CONTACT AREA: G/F SOLDER AREA: Sn	

SIDE	DATE	DESCRIPTION	APPROVER
△	2009/09/04	NEW ISSUE	JINGLI

QUALITY SYMBOLS	Tolerance
□: CRITICAL	x. ±0.50
⊠: MAJOR	.x ±0.30
▽: ZERO DEFECT	.xx ±0.25
S.P.C	

NAME:	D-SUB 公头一体焊线式前铆5.8实芯螺母 (客户用图)				PART NO.	B05-0XX3X1A0-F5	
REV:	A	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.
SCALE:	N:1	DATE:	2009/09/04	JINGLI	KING ZHOU		B05-087

lineconn 东莞市林诚塑胶电子有限公司 <http://www.lineconn.com>
 TEL: 0769-85181660 85181770