

No. of Contact	A	B	C	D
15	16.9	25.0	30.8	19.3
26	25.2	33.3	39.1	27.5
44	39.0	47.0	53.0	41.3
62	55.4	63.5	69.3	57.7

Voltage Current Rating: 5 AMP.  
 Dielectric Withstanding Voltage: 1000V AC  
 Insulation Resistance: 1000M $\Omega$  Min.  
 Temperature Range: -25°C to +85°C

PART NO: B04-0XX3X14N-02

NO.OF CONTACT:  
 15 = 15 pos  
 26 = 26 pos  
 44 = 44 pos  
 62 = 62 pos

HOUSING COLOR:  
 1 = BLACK  
 5 = WHITE  
 6 = BLUE


4	REAR SHELL	SPCC	PALTING: Sn
3	FRONT SHELL	SPCC	PALTING: Ni
2	HOUSING	PBT+30%GF	COLOR: SEE PART NO.
1	TERMINAL	COPPER ALLOY	TERMINAL FINISH: FULL GOLD FINISHED 2u"
ITEM	DESC.	MATERIAL	REMAKS

QUALITY SYMBOLS

□: CRITICAL  
 ▽: ZERO DEFECT  
 ☒: MAJOR  
 ▽: S.P.C

Tolerance

x:  $\pm 0.50$   
 .x:  $\pm 0.30$   
 .xx:  $\pm 0.25$



NAME:		HD.D-SUB 公头车针焊线式 (客户用图)				PART NO.		B04-0XX3X14N-02	
REV:	A	UNIT:	mm	DRW BY:	JINGLI	CHK BY:	KING ZHOU	APP BY:	
SCALE:	N:1	DATE:	2009/04/14						B04-001

lineconn 东莞市林诚塑胶电子有限公司 <http://www.lineconn.com>  
 TEL: 0769-85181660 85181770

SIDE	DATE	DESCRIPTION	APPROVER
△	2009/04/14	NEW ISSUE	JINGLI