


ELECTRICAL CHARACTERISTICS

Contact Current Rating: 3 Amp
 Dielectric Withstanding Voltage: 500V AC
 Insulation Resistance: 500MΩ/Min
 Contact Resistance: 35mΩ/Max
 Operation Temperature: -25°C ~ +85°C



ITEM	DESC.	MATERIAL	REMARKS	PART REMARKS
3	NUT	COPPER ALLOY		
2	HOUSING	PBT+30%GF	COLOR:BLACK	
1	TERMINAL	COPPER ALLOY	PLATING:GOLD FLASH/TIN	

QUALITY SYMBOLS		Tolerance		NAME: FCN 40P MALE 180° DIP				PART NO.	B01-04071NA4-01		
△		□ :	±0.80	REV:	A	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.
△		CRITICAL	±0.50	SCALE:	N:1	DATE:	2019/11/23	Huangmei	Jack Chen		B01-037
△	2019/11/23	NEW ISSUE	±0.30	Lineconn 东莞市林诚塑胶电子有限公司 http://www.lineconn.com TEL:0769-85181660 85181770							
SIDE	DATE	DESCRIPTION	APPROVER								
8	7	6	5	4	3	2	1				