



**ELECTRICAL CHARACTERISTICS**  
 Contact Current Rating: 3 Amp  
 Dielectric Withstanding Voltage: 500V AC  
 Insulation Resistance: 500MΩ/Min  
 Contact Resistance: 35mΩ/Max  
 Operation Temperature: -25°C ~ +85°C

ITEM	DESC.	MATERIAL	REMARKS	PART REMARKS
5	SCREW	STEEL	PLATING:NI	
5	CLIP WIRE LATCH	STEEL	PLATING:NI	
4	SHIELD	ZINC ALLOY	PLATING:NI	
3	SHELL	ZINC ALLOY	PLATING:NI	
2	HOUSING	LCP+30%GF	COLOR:BLACK	
1	TERMINAL	COPPER ALLOY	PLATING:GOLD FLASH/TIN	

△				QUALITY SYMBOLS	Tolerance	NAME:	HD-VI 28P公头焊线式锌合金外壳组装				PART NO.	B06-028318C8-01	
△				□:    ☒:	x.    ±0.60	REV:	A	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.
△	2020/11/23	NEW ISSUE	Jack Chen	CRITICAL    MAJOR	.x    ±0.40	SCALE:	N:1	DATE:	2020/11/23	Huangmei	Jack Chen		B06-021
SIDE	DATE	DESCRIPTION	APPROVER	▽:    ▽:	.xx    ±0.25	 东莞市林诚塑胶电子有限公司 <a href="http://www.lineconn.com">http://www.lineconn.com</a> TEL:0769-85181660 85181770							

8	7	6	5	4	3	2	1
---	---	---	---	---	---	---	---