



Detail A Scale 1.5:1

ELECTRICAL:

- Current Rating: 0.5 Amp
- Insulation Resistance: 500MΩ/Min
- Withstanding Voltage: 250V AC
- Contact Resistance: 35mΩ Max
- Temperature Range: -25°C ~ +85°C

3	HOUSING	PBT+30%GF	COLOR:BLACK	
2	SHELL	SPCC	PLATING:Ni	
1	TERMINAL	PHOSPHOR BRONZE	CONTACT AREA:Au 5u" SOLDER AREA:Sn UNDER-PLATING:Ni	
ITEM	DESC.	MATERIAL	REMARKS	PART REMARKS

				QUALITY SYMBOLS	Tolerance	NAME: VHDCI 68P MALE夹板式 (客户用图)				PART NO.	B06-068G11EN-01		
				□: CRITICAL	x. ±0.50	REV:	A	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.
				⊕: MAJOR	.x ±0.30	SCALE:	N:1	DATE:	2018/06/03	FEI CHEN	KING ZHOU		B06-018
				▽: ZERO DEFECT	.xx ±0.25	lineconn 东莞市林诚塑胶电子有限公司				http://www.lineconn.com			
				▽: S.P.C		TEL:0769-85181660 85181770							
SIDE	DATE	DESCRIPTION	APPROVER										

				QUALITY SYMBOLS	Tolerance	NAME: VHDCI 68P MALE夹板式 (客户用图)				PART NO.	B06-068G11EN-01		
				□: CRITICAL	x. ±0.50	REV:	A	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.
				⊕: MAJOR	.x ±0.30	SCALE:	N:1	DATE:	2018/06/03	FEI CHEN	KING ZHOU		B06-018
				▽: ZERO DEFECT	.xx ±0.25	lineconn 东莞市林诚塑胶电子有限公司				http://www.lineconn.com			
				▽: S.P.C		TEL:0769-85181660 85181770							
SIDE	DATE	DESCRIPTION	APPROVER										