



截面A-A

技术参数:

1. 材料符合环保要求, 连接器对插符合IEC 61076-2-101
2. 连接器防护等级: IP67
3. 工作温度:  $-25^{\circ}\text{C} \sim +85^{\circ}\text{C}$
4. 机械寿命:  $>500$ 次插拔
5. 额定电压: 60V
6. 额定电流: 4A
7. 触点电阻:  $3\text{m}\Omega / \text{Max}$

序号	名称	材料
5	铜管	H59
4	端子	Qsn4-3
3	绝缘体	PA66
2	O型圈	NBR
1	外壳	H59

				QUALITY SYMBOLS		Tolerance		NAME: M8 3P A扣公头焊线式			PART NO. B10-M080T030-01	
				□: CRITICAL	☒: MAJOR	x: ±0.60		REV: A	UNIT: mm	DRW BY	CHK BY	DRAWING NO.
△		2017/03/26	NEW ISSUE	Jack Chen		.x ±0.40		SCALE: N:1	DATE: 2017/03/26	Huangmei	Jack Chen	B10-041
SIDE		DATE	DESCRIPTION	APPROVER		.xx ±0.25		lineconn 东莞市林诚塑胶电子有限公司			http://www.lineconn.com	
8		7	6	5	4	ZERO DEFECT S.P.C			TEL:0769-85181660 85181770			1