



Contact Current Rating: 5Amp  
 Dielectric Withstanding Voltage: 500V AC  
 Insulation Resistance: >1000 mΩ/Min  
 Contact Resistance: 30mΩ/Max  
 Operation Temperature: -55°C ~ +105°C

5	SCREWS	STEEL	PLATING: Ni
4	BACK SHELL	STEEL	PLATING: Ni
3	FRONT SHELL	STEEL	PLATING: Ni
2	HOUSING	PBT UL94V-0	COLOR: BLUE
1	TERMINAL	COPPER ALLOY	CONTACT AREA: G/F SOLDER AREA: Sn
ITEM	DESC.	MATERIAL	REMARK

△	2022/11/29	Change the size of the iron casing	Jack Chen
△	2016/03/09	Mark screw specification	JINGLI
△	2012/07/12	New version release	JINGLI
SIDE	DATE	DESCRIPTION	APPROVER
8	7	6	5

QUALITY SYMBOLS		Tolerance	
□:	☒:	.x	±0.60
CRITICAL	MAJOR	.x	±0.40
▽:	▽:	.xx	±0.25
ZERO DEFECT	S.P.C		

NAME:	57-80500 50P母头焊线式+90度牙刷铁壳				PART NO.	B17-050361AD-01			
REV:	C	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.		
SCALE:	N:1	DATE:	2012/07/12	Huangmei	Jack Chen	B17-017			
				<b>东莞市林诚塑胶电子有限公司</b>				<a href="http://www.lineconn.com">http://www.lineconn.com</a> TEL: 0769-85181660 85181770	
8	7	6	5	4	3	2	1		