



截面 A-A

Voltage Current Rating: 1.5 AMP.40V AC
 Dielectric Withstanding Voltage: 500V AC
 Contact Resistance: 30 mΩ Max.
 Insulation Resistance: 100MΩ Min.
 Temperature Range: -25°C to +85°C

4	COVER	COPPER ALLOY	OVER-PLATING: Ni	
3	SHELL	COPPER ALLOY	OVER-PLATING: Ni	
2	HOUSING	PBT UL94V-0	COLOR: BLACK	
1	CONTACT	COPPER ALLOY	CONTACT AREA: G/F SOLDER AREA: G/F UNDER-PLATING: Ni	
ITEM	DESC.	MATERIAL	REMARKS	PART REMARKS

△				QUALITY SYMBOLS	Tolerance	NAME:	SM 6P母座侧插				PART NO.	B19-006A13AN-01	
△	2021/03/02	增加电气性能描述	JACK CHEN	□: ☒:	x. ±0.60	REV:	B	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.
△	2011/07/02	新版发行	JING LI	CRITICAL MAJOR	.x ±0.40	SCALE:	NONE	DATE:	2011/07/02	JING LI	JACK CHEN		B19-005
SIDE	DATE	DESCRIPTION	APPROVER	▽: ▽:	.xx ±0.25	Lineconn 东莞市林诚塑胶电子有限公司				http://www.lineconn.com			
8	7	6	5	ZERO DEFECT S.P.C		TEL:0769-85181660 85181770							

东莞市林诚塑胶电子有限公司

http://www.lineconn.com

TEL:0769-85181660 85181770