



Voltage Current Rating: 20 AMP.
Dielectric Withstanding Voltage: 1000V AC
 Insulation Resistance: 1000MΩ Min.
 Temperature Range: -25°C to +85°C

7	SCREW	STEEL	PALTING: Ni	
6	PCB	FR4		
5	HOOD	PA66 GF.30%	COLOR: BLACK	
4	REAR SHELL	SPCC	PALTING: Ni	
3	FRONT SHELL	SPCC	PALTING: Ni	
2	HOUSING	PBT+30%GF	COLOR: BLACK	
1	TERMINAL	COPPER ALLOY	CONTACT AREA: G/F SOLDER AREA: G/F UNDER-PLATING: Ni	
ITEM	DESC.	MATERIAL	REMAKS	REMAKS

				QUALITY SYMBOLS		Tolerance		NAME: D-SUB 9P FEMALE POGO PIN TYPE R/A(A款 (客户用图))		PART NO. B05-009611ND-MA	
				□: ☒:		x. ±0.50		REV: A		UNIT: mm	
				CRITICAL MAJOR		.x ±0.30		SCALE: N:1		DATE: 2018/07/13	
				▽: ▽:		.xx ±0.25		DATE: 2018/07/13		JINGLI	
SIDE		DATE		DESCRIPTION		APPROVER		JINGLI		KING ZHOU	
8		7		6		5		4		3	
								Lineconn		东莞市林诚塑胶电子有限公司	
										http://www.lineconn.com	
										TEL: 0769-85181660 85181770	
										1	