


**Voltage Current Rating: 20 AMP.**  
**Dielectric Withstanding Voltage: 1000V AC**  
 Insulation Resistance: 1000MΩ Min.  
 Temperature Range: -25°C to +85°C

6	PCB	FR4		
5	HOOD	PA66 GF.30%	COLOR: BLACK	
4	REAR SHELL	SPCC	PALTING: Ni	
3	FRONT SHELL	SPCC	PALTING: Ni	
2	HOUSING	PBT+30%GF	COLOR: BLACK	
1	TERMINAL	COPPER ALLOY	CONTACT AREA: G/F SOLDER AREA: G/F UNDER-PLATING: Ni	
ITEM	DESC.	MATERIAL	REMAKS	REMAKS

				QUALITY SYMBOLS		Tolerance		NAME: D-SUB 9P FEMALE POGO PIN TYPE R/A (B款 M2.6)			PART NO. B05-009611ND-MB			
				□:      ☒:		x.      ±0.50		REV: A	UNIT: mm	(客户用图) DRW BY		CHK BY	APP BY	DRAWING NO.
△		2018/07/17	NEW ISSUE	JINGLI	CRITICAL MAJOR	.x      ±0.30		SCALE: N:1	DATE: 2018/07/17	JINGLI	KING ZHOU	B05-067		
SIDE	DATE	DESCRIPTION		APPROVER	▽:      ▽:	.xx      ±0.25		 东莞市林诚塑胶电子有限公司			<a href="http://www.lineconn.com">http://www.lineconn.com</a> TEL: 0769-85181660 85181770			
8	7	6	5	4	3	2	1							