



No. of Contact	A	B	C	D
09	16.9	25.0	30.8	19.3
15	25.2	33.3	39.1	27.5
25	39.0	47.0	53.0	41.3
37	55.4	63.5	69.3	57.7

Voltage Current Rating: 5 AMP.  
 Dielectric Withstanding Voltage: 1000V AC  
 Insulation Resistance: 1000MΩ Min.  
 Δ Temperature Range: -55°C to +105°C

PART NO: B05-0XX3X1XN-02

NO.OF CONTACT: 9P, 15P, 25P, 37P  
 HOUSING COLOR: 1: BLACK, 5: WHITE, 6: BLUE  
 TERMINAL PLATING: 4: FULL Au 2u", 5: FULL Au 1u"

ITEM	DESC.	MATERIAL	REMARKS	PART REMARKS
4	REAR SHELL	SPCC	PALTING: Sn	
3	FRONT SHELL	SPCC	PALTING: Ni	
2	HOUSING	PBT+30%GF	COLOR: SEE PART NO.	
1	TERMINAL	COPPER ALLOY	PLATING: SEE PART NO.	

SIDE	DATE	DESCRIPTION	APPROVER
△	2023/08/16	Modified operating temperature	Jack Chen
△	2022/03/26	Added specifications for terminal plating	Jack Chen
△	2009/04/14	NEW ISSUE	JINGLI

QUALITY SYMBOLS	Tolerance
□ : CRITICAL ▽ : ZERO DEFECT	x. ±0.60 .x ±0.40 .xx ±0.25
☒ : MAJOR ▽ : S.P.C	

NAME:	D-SUB公头车针焊线式				PART NO.	B05-0XX3X1XN-02		
REV:	C	UNIT:	mm	DRW BY:	CHK BY:	APP BY:	DRAWING NO.	
SCALE:	N:1	DATE:	2009/04/14	Huangmei	Jack Chen	B05-014		
lineconn 东莞市林诚塑胶电子有限公司				http://www.lineconn.com				
				TEL: 0769-85181660 85181770				