



High Power Current Rating:10,20 or 40 AMP.
 High Power Current Resistance:2.7 Milliohms MAX.
 Dielectric Withstanding Voltage:1000V AC
 Insulation Resistance:5000M Ω Min.
 Δ Temperature Range:-55°C to +105°C

PART NO:

B08-3W3311XN-X0

Δ Terminal plating:

- 4 = full gold 2u"
- 5 = full gold 1u"

Current rating:

- A = 10 AMPS Dim.A ϕ 1.70
- B = 20 AMPS Dim.A ϕ 2.80
- C = 30 AMPS Dim.A ϕ 3.30
- D = 40 AMPS Dim.A ϕ 4.60

4	REAR SHELL	SPCC	PALTING:Sn	
3	FRONT SHELL	SPCC	PALTING:Ni	
2	HOUSING	PBT+30%GF	COLOR:BLACK	
1	TERMINAL	COPPER ALLOY	PALTING:SEE PART NO.	
ITEM	DESC.	MATERIAL	REMAKS	PART REMAKS

Δ	2023/08/17	1,Added the terminal plating type 2,Modified operating temperature	Jack Chen
Δ	2013/03/11	NEW ISSUE	JINGLI
SIDE	DATE	DESCRIPTION	APPROVER
8	7	6	5

QUALITY SYMBOLS		Tolerance	
\square :	\boxtimes :	x.	\pm 0.60
CRITICAL	MAJOR	.x	\pm 0.40
∇ :	∇ :	.xx	\pm 0.25
ZERO DEFECT	S.P.C		

NAME:		3W3公头焊线式光孔POWER D-SUB (客户用图)				PART NO.	B08-3W3311XN-X0	
REV:	B	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.	
SCALE:	N:1	DATE:	2013/03/11	Huangmei	Jakc Chen		B08-005	
东莞市林诚塑胶电子有限公司				http://www.lineconn.com TEL:0769-85181660 85181770				
8	7	6	5	4	3	2	1	