



Pin contact style only
 Soldering termination only
 Conductor size: 20 AWG Max.
 Individually waterproof

SPECIFICATIONS

Rated Current: 3A Max. / Contact
 Rated Voltage: 200V AC(r.m.s.) Max.
 Dielectric Withstanding Voltage:
 1500V AC(r.m.s.) / 1 minute (2Pin)
 900V AC(r.m.s.) / 1 minute (10Pin)
 Insulation Resistance: 1000M Ω Min. at 500V DC
 Operating Temperature Range: -25℃ to +85℃
 Conductor Size: # 22
 Protection Rate: IP67 when mated (Receptacle : Individually waterproof)

7	Ground Lug	Copper Alloy	Gold Plating
6	Retaining Ring	Copper Alloy	Gold Plating
5	Receptacle Shell	Zinc Alloy	Nickel Plating
4	O Ring	Synthetic Rubber	Color:Black
3	Pin Contact	Copper Alloy	Gold Plating
2	Pin Rear Insulator	Plastic(UL94V-0)	Color:Black
1	Pin Front Insulator	Synthetic Rubber	Color:Black
ITEM	DESC.	MATERIAL	REMARKS

A	△			QUALITY SYMBOLS	Tolerance	NAME:	CM10 2Pin Socket For Panel Mount			PART NO.	B01-CM10R2P(D3)-01		
	△			□: ⊠:	.x ±0.60	REV:	A	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.
	△	2022/03/07	新版发行	CRITICAL MAJOR	.x ±0.40	SCALE:	N:1	DATE:	2022/03/07	Huangmei	Jack Chen		B01-062
	△			▽: ▽:	.xx ±0.25								
	SIDE	DATE	DESCRIPTION	APPROVER	ZERO DEFECT S.P.C	东莞市林诚塑胶电子有限公司			http://www.lineconn.com TEL:0769-85181660 85181770				
	8	7	6	5	4	3	2	1					