



Pin contact style only  
 Soldering termination only  
 Conductor size: 20 AWG Max.  
 Individually waterproof

**SPECIFICATIONS**

Rated Current: 3A Max. / Contact  
 Rated Voltage: 200V AC(r.m.s.) Max.  
 Dielectric Withstanding Voltage:  
 1500V AC(r.m.s.) / 1 minute (2Pin)  
 900V AC(r.m.s.) / 1 minute (10Pin)  
 Insulation Resistance: 1000M Ω Min. at 500V DC  
 Operating Temperature Range: -25℃ to +85℃  
 Conductor Size: # 22  
 Protection Rate: IP67 when mated (Receptacle : Individually waterproof)

7	Ground Lug	Copper Alloy	Gold Plating
6	Retaining Ring	Copper Alloy	Gold Plating
5	Receptacle Shell	Zinc Alloy	Nickel Plating
4	O Ring	Synthetic Rubber	Color:Black
3	Pin Contact	Copper Alloy	Gold Plating
2	Pin Rear Insulator	Plastic (UL94V-0)	Color:Black
1	Pin Front Insulator	Synthetic Rubber	Color:Black
ITEM	DESC.	MATERIAL	REMARKS

A	△			QUALITY SYMBOLS	Tolerance	NAME:	CM10 10Pin Socket For Panel Mount			PART NO.	B01-CM10R10P(D3)-01		
	△			□:    ☒:	.x    ±0.60	REV:	A	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.
	△	2022/03/07	新版发行	CRITICAL    MAJOR	.x    ±0.40	SCALE:	N:1	DATE:	2022/03/07	Huangmei	Jack Chen		B01-061
	△			▽:    ▽:	.xx    ±0.25	东莞市林诚塑胶电子有限公司    http://www.lineconn.com TEL:0769-85181660 85181770							
	SIDE	DATE	DESCRIPTION	APPROVER	ZERO DEFECT    S.P.C								