

SECTION A-A

TECHNICAL PARAMETER:

1. ROHS environmental protection
2. Connector protection grade: IP67
3. Temperature Range: -25° +85° C
4. Mechanical life: >500 times of plugging and unplugging
5. Rated voltage: 250V
6. Contact Current Rating: 4A
7. Contact Resistance: 3mΩ /Max


11	NUT	PA
10	CABLE CLIP	PA
9	SEALING RINGS	NBR
8	HOOD	PA
7	SCREW	STAINLESS STEEL
6	HOUSING	PA
5	SEALING RINGS	NBR
4	NUT	PA
3	SEALING RINGS	NBR
2	TERMINAL	COPPER ALLOY
1	HOOD	ZINC ALLOY
ITEM	DESC.	MATERIAL

QUALITY SYMBOLS

□: ☒: CRITICAL MAJOR
 ▽: ▽: ZERO DEFECT S.P.C

Tolerance

x. ±0.60
 .x ±0.40
 .xx ±0.25



NAME: M12 4P A coding female screw clamp PA hood assembly type

REV: A

SCALE: N:1

PART NO. B10-M12H04A0-2C

UNIT: mm DRW BY: Jack Chen CHK BY: Jack Chen APP BY: DRAWING NO. B10-059

DATE: 2018/03/26 Huangmei Jack Chen

Lineconn

Dongguan Lineconn

http://www.lineconn.com
 TEL:0769-85181660 85181770

△	2018/03/26	NEW ISSUE	Jack Chen
SIDE	DATE	DESCRIPTION	APPROVER
8	7	6	5

3 2 1