

No. of Contact	A ±0.25 ±.010	B ±0.13 ±.005	C ±0.38 ±.015	D ±0.25 ±.010	E
09	16.90	25.00	30.80	19.28	11.08
15	25.35	33.30	39.20	27.51	19.39
25	39.00	47.04	53.04	41.28	33.24
37	55.42	63.50	69.40	57.71	49.86

Voltage Current Rating:5 AMP.
 Dielectric Withstanding Voltage:1000V AC
 Insulation Resistance:1000MΩ Min.
 Temperature Range:-55°C to +105°C

PART NO:
 B05-0XX7X1XD-02

No.of contact:
 09:9 pos
 15:15 pos
 25:25 pos
 37:37 pos
 Housing color:
 1:Black
 5:White
 6:Blue
 Terminal plating:
 4:Full gold 2u"
 5:Full gold 1u"


ITEM	DESC.	MATERIAL	REMARKS
6	SCREW	STEEL	PALTING: Ni
5	BOARDLOCK	COPPER ALLOY	PALTING: Ni
4	HOUSING	PBT+30%GF	COLOR: SEE PART NO.
3	REAR SHELL	SPCC	PALTING: Sn
2	FRONT SHELL	SPCC	PALTING: Ni
1	TERMINAL	COPPER ALLOY	PALTING: SEE PART NO.

QUALITY SYMBOLS

□: □: CRITICAL MAJOR
 ▽: ▽: ZERO DEFECTS.P.C

Tolerance

.x ±0.60
 .x ±0.40
 .xx ±0.25



NAME: D-SUB 车针公头180度直插, 后铆6.0铜柱, 前锁4.8螺母 PART NO. B05-0XX7X1XD-02

REV: A UNIT: mm DRW BY: CHK BY: APP BY: DRAWING NO. B05-179

SCALE: N:1 DATE: 2019/04/11 Huangmei Jack Chen

lineconn 东莞市林诚塑胶电子有限公司 http://www.lineconn.com
 TEL: 0769-85181660 85181770

SIDE	DATE	DESCRIPTION	APPROVER
△	2019/04/11	NEW ISSUE	Jack Chen