



P.C.B LAYOUT

No. of Contact	3		2		1
	A ±0.25 ±.010	B ±0.13 ±.005	C ±0.38 ±.015	D ±0.25 ±.010	E
09	16.30	25.00	30.80	19.28	11.08
15	24.80	33.30	39.20	27.51	19.39
25	38.30	47.04	53.04	41.28	33.24
37	54.80	63.50	69.32	57.71	49.86

Voltage Current Rating:5 AMP.
 Dielectric Withstanding Voltage:1000V AC
 Insulation Resistance:1000MΩ Min.
 Temperature Range:-55°C to +105°C

PART NO:
 B05-0XX8X1XD-02

No.of contact:
 09:9 pos
 15:15 pos
 25:25 pos
 37:37 pos
 Housing color:
 1:Black
 5:White
 6:Blue
 Terminal plating:
 4:Full gold 2u"
 5:Full gold 1u"

ITEM	DESC.	MATERIAL	REMAKS	PART REMAKS
6	SCREW	STEEL	PALTING: Ni	
5	BOARDLOCK	COPPER ALLOY	PALTING: Ni	
4	HOUSING	PBT+30%GF	COLOR: SEE PART NO.	
3	REAR SHELL	SPCC	PALTING: Sn	
2	FRONT SHELL	SPCC	PALTING: Ni	
1	TERMINAL	COPPER ALLOY	PALTING: SEE PART NO.	

SIDE	DATE	DESCRIPTION	APPROVER
8	2019/04/11	NEW ISSUE	Jack Chen

QUALITY SYMBOLS	Tolerance
□: CRITICAL ▽: ZERO DEFECTS.P.C	x. ±0.60 .x ±0.40 .xx ±0.25

NAME:	D-SUB 车针母头180度直插, 后铆6.0铜柱, 前锁4.8螺母				PART NO.	B05-0XX8X1XD-02			
REV:	A	UNIT:	mm	DRW BY:	Huangmei	CHK BY:	Jack Chen	APP BY:	
SCALE:	N:1	DATE:	2019/04/11			DRAWING NO. B05-177			
东莞市林诚塑胶电子有限公司				http://www.lineconn.com TEL: 0769-85181660 85181770					