



RECOMMENDED P.C.B LAYOUT

Voltage Current Rating:5 AMP.
 Dielectric Withstanding Voltage:1000V AC
 Insulation Resistance:1000M Ω Min.
 Temperature Range:-25 $^{\circ}$ C to +85 $^{\circ}$ C

PART NO:
 B05-0788X15D-02
 HOUSING COLOR:
 1 = BLACK
 5 = WHITE

ITEM	DESC.	MATERIAL	REMARKS	PART REMARKS
6	SCREW	STEEL	PALTING: Ni	
5	BOARDLOCK	COPPER ALLOY	PALTING: Ni	
4	HOUSING	PBT+30%GF	COLOR: SEE PART NO.	
3	REAR SHELL	SPCC	PALTING: Sn	
2	FRONT SHELL	SPCC	PALTING: Ni	
1	TERMINAL	COPPER ALLOY	PALTING: FULL GOLD FLASH	

SIDE	DATE	DESCRIPTION	APPROVER
A	2023/03/08	NEW ISSUE	Jack Chen

QUALITY SYMBOLS	Tolerance
□: CRITICAL ▽: ZERO DEFECT	x. ± 0.60 .x ± 0.40 .xx ± 0.25

NAME:	HD. D-SUB 78P车针母头180度直插, 铆铜柱锁螺丝	PART NO.	B05-0788X15D-02
REV:	A	UNIT:	mm
SCALE:	N:1	DATE:	2023/03/08
DRW BY:	Huangmei	CHK BY:	Jack Chen
APP BY:		DRAWING NO.:	B05-156

lineconn 东莞市林诚塑胶电子有限公司 <http://www.lineconn.com>
 TEL:0769-85181660 85181770