



No.of contacts:	A	B	C
26	24.00	20.25	9.30
36	30.40	26.50	8.60
50	39.20	35.50	9.30
68	50.90	46.93	9.30

Current rating: 1 AMP.
 Withstanding voltage: 500V AC
 Insulation resistance: 500MΩ Min.
 Contact resistance: 35mΩ max.
 Temperature range: -45°C to +105°C
 ROHS compliant
 Part number:

B03-0XX411EN-01

No.of contacts: _____
 26: 26pin
 36: 36pin
 50: 50pin
 68: 68pin

4	Cover	PBT+30%GF	Color:black
3	Housing	PBT+30%GF	Color:black
2	Shell	SPCC	Plating:Ni
1	Terminal	Phosphor bronze	Contact area:Au 5u" Solder area:Sn Under-plating:Ni
Item	Desc.	Material	Remark

△	2023/03/19	Change tolerance	Carl Hu
△	2021/07/10	Change part number	Jack Chen
△	2014/11/07	First edition release	Jing Li

QUALITY SYMBOLS		Tolerance	
□:	☒:	x.	±0.60
CRITICAL	MAJOR	.x	±0.40
▽:	▽:	.xx	±0.25
ZERO DEFECT	S.P.C		

NAME:	SCSI(HPCN) female solder assembly connector(26,36,50,68pin)				PART NO.	B03-0XX411EN-01		
REV:	D	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.	
SCALE:	N:1	DATE:	2014/11/07	Yugong	Carl Hu		B03-017	

lineconn 东莞市林诚塑胶电子有限公司 <http://www.lineconn.com>
 TEL:0769-85181660 85181770

8	7	6	5	4	3	2	1
F							F
E							E
D							D
C							C
B							B
A							A
8	7	6	5	4	3	2	1