



Rated current: 1A  
 Rated voltage: 100VAC rms  
 Withstand voltage: 500VAC(r.m.s.)/ 1minute  
 Insulation resistance: 500M Ω Min. at 500VDC  
 Operating temperature: -20℃ to 105℃  
 Protection grade: IP67

9	Screw	Steel	Color:black	2pcs
8	Shrapnel	Stainless steels		2pcs
7	Encoder terminal	Phosphor bronze	Plating: Au	7pcs
6	Plastic ring	PA66+30%GF UL94V-0	Color:black	2pcs
5	Sealing ring	Rubber	Color:black	1pcs
4	Sealing gasket	Rubber	Color:black	1pcs
3	Inner housing	PA66+30%GF UL94V-0	Color:black	1pcs
2	Plastic nut	PA66+30%GF UL94V-0	Color:black	1pcs
1	Plastic hood	PA66+30%GF UL94V-0	Color:black	1pcs
Item	Desc.	Material	Remark	Quantity

A	△			QUALITY SYMBOLS	Tolerance x. ±0.60 .x ±0.40 .xx ±0.25	NAME: JN01-07P servo encoder plug				PART NO.	B01-JN01007P-01	
	△	2025/05/21	Changed tolerance	Jack Chen		REV: B	UNIT: mm	DRW BY	CHK BY	APP BY	DRAWING NO. B01-060	
	△	2022/03/07	First edition release	Jack Chen		CRITICAL MAJOR	SCALE: N:1	DATE: 2022/03/07	Huangmei	Jack Chen		
	SIDE	DATE	DESCRIPTION	APPROVER		ZERO DEFECT S.P.C	<b>东莞市林诚塑胶电子有限公司</b>				<a href="http://www.lineconn.com">http://www.lineconn.com</a> TEL:0769-85181660 85181770	
	8	7	6	5	4	3	2	1				