



PCB layout

Current rating: 1A
 Withstanding voltage: 500V AC
 Contact resistance : 35mΩ max.
 Insulation resistance: 500MΩ Min.
 Temperature range: -45°C to +105°C
 ROHS compliant

3	Housing	PBT+G.F.30%	Color:black
2	Shell	SPCC	Plating:Ni
1	Terminal	Phosphor bronze	Contact area:Au 5u" Solder area:Sn Under-plating:Ni
Item	Desc.	Material	Remark

△	2021/07/04	Change part number	Carl Hu
△	2014/11/21	Change tolerance	King Zhou
△	2009/06/12	First edition release	King Zhou
SIDE	DATE	DESCRIPTION	APPROVER

QUALITY SYMBOLS		Tolerance	
□ :	☒ :	.x	±0.60
CRITICAL	MAJOR	.x	±0.40
▽ :	▽ :	.xx	±0.25
ZERO DEFECT	S.P.C	 	

NAME:	SCSI(HPCN) 50pin male vertical for PCB			PART NO.	B03-050711EN-01		
REV:	C	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.
SCALE:	N:1	DATE:	2009/06/12	Yugong	Carl Hu		B03-065
 东莞市林诚塑胶电子有限公司				http://www.lineconn.com TEL:0769-85181660 85181770			