



Current rating: 1A  
 Withstanding voltage: 500V AC  
 Contact resistance : 35mΩ max.  
 Insulation resistance: 500MΩ Min.  
 Temperature range: -45℃ to +105℃  
 ROHS compliant

3	Housing	PBT+G.F.30%	Color: black
2	Shell	SPCC	Plating: Ni
1	Terminal	Phosphor bronze	Contact area: Au 5u" Solder area: Sn Under-plating: Ni
Item	Desc.	Material	Remark

△	2021/07/04	Change part number	Carl Hu
△	2014/11/21	Change tolerance	King Zhou
△	2009/06/12	First edition release	King Zhou
SIDE	DATE	DESCRIPTION	APPROVER
8	7	6	5

QUALITY SYMBOLS	Tolerance	NAME:	SCSI(HPCN) 26pin male vertical for PCB			PART NO.	B03-026711EN-01		
□:      ☒:	x.      ±0.60	REV:	C	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO. B03-052
CRITICAL MAJOR	.x      ±0.40	SCALE:	N:1	DATE:	2009/06/12	Yugong	Carl Hu		
▽:      ▽:	.xx      ±0.25								
ZERO DEFECT S.P.C									

**lineconn** 东莞市林诚塑胶电子有限公司 <http://www.lineconn.com>  
 TEL: 0769-85181660 85181770